Eventlabel	DDU2005_emp_a_f_19		
Campaign	Dumont d´Urville, Terre Adélie, 2005		
Species	Emperor penguin (<i>Aptenodytes forsteri</i>)		
Age	≥ 4 years		
Sex	우 · · · · · · · · · · · · · · · · · · ·		
Number			
	19(V)		
Length			
Girth			
Weight [estimated]			
Weight [calculated]	<u></u>		
Weight [measured]	?		
ARGOS PTT ID	60047		
Transmitter type	SPLASH Satellite T	ransmitter	
	17 cm 5 cm B cm		
Manufacturer	Wildlife Computers		
PTT Serial Number	05L0056		
PTT Software	SplashHost.1.00.0	017	
Setting protocol			
51		Host Settings	
	SplashHost version	1.00.0017	
	User Name	Mb	
		Time And Date Settings	
	PC Date	Time And Date Settings 23 Nov 2005 at 11:24:41	
	Tag Date	23 Nov 2005 at 01:25:46	
		General Settings	
	Tag's Serial Number	05L0056	
	Password	SPLASH	
	User's Identifier	DDU2005_emp_a_f_19 60047 (08C54F2 Hex) Uplink / LUT id: 561:242	
	Argos Ptt number Repitition Intervals	39s (at-sea); 89s (haulout)	
	Tagware version	1.00h	
	Hardware version		
	Owner	Ilka Zimmer Marine Animal Ecology Alfred Wegener Institute for Polar and Marine Research	
	Data to Archive Settings		

[]	Depth	2 seconds
	Temperature	2 seconds
	Light Level	10 seconds
	Battery Voltage	never
	Wet/Dry Sensor	10 seconds
	Sampling Mode	Archive samples when tag is wet or dry
	Wet/Dry Threshold	Dry if > 150
	Stabilization Time	3ms
	Sampling Duration	Time till 15 MByte memory is filled is 75 days
	bumphing Duration	The diff is highly to highly is finded is 75 days
	Data to Transmit Settings	
	Histogram Data sampling interval	1 seconds
	Dive Maximum Depth (m), 14 bins	50, 100, 150, 200, 250, 300, 350, 400, 450, 500, 550, 600, 650, >650
	Dive Duration (sec), 14 bins	60, 120, 180, 240, 300, 360, 420, 480, 540, 600, 660, 720, 780, >780
	Time-at-Temperature (C), 14 bins	-20, -15, -10, -5, -2, -1.7, -1.4, -1.1, -0.8, -0.5, -0.2, 0.1, 5, >5
	Time-at-Depth (m), 14 bins	50, 100, 150, 200, 250, 300, 350, 400, 450, 500, 550, 600, 650, >650
	Hourly % time-line	Enabled
	Histogram Callaction	
	Histogram Collection	
	Hours of data summarized in each histogram	6
	Histograms start at GMT	01:00
	Dive & Timeline Definition	
	Depth reading to determine start and end of dive	2m
	Ignore dives shallower than	2m
	Depth threshold for timelines	0.5m
	Haulout Definition	
	A minute is "dry" if Wet/Dry sensor is dry for any <i>value</i> seconds in a minute	30
	Enter haulout state after <i>value</i> consecutive dry minutes	20
	Exit haulout state if wet for any <i>value</i> seconds in a minute	20
	Transmission Control	Γ
	Transmit data collected over these last days	2
	Pause transmissions if haulout exceeds	12 hours
	Transmit every eighth day if transmissions are paused	Disabled
	When to Transmit Settings	
	Transmit for the first 24 hours regardless of settings	Enabled

below			
Transmit hours	0 - 23		
	0 - 23		
Transmit days	Transmit days		
January	1 - 31		
February	1 - 28		
March	1 - 31		
April	1 - 30		
May	1 - 31		
June	1 - 30		
July	1 - 31		
August	1 - 31		
September	1 - 30		
October	1 - 31		
November	1 - 30		
December	1 - 31		
Daily Transmit Allowan	ce		
January	320 [Accumulate, DO NOT Optimize for battery life]		
February	320 [Accumulate, DO NOT Optimize for battery life]		
March	320 [Accumulate, DO NOT Optimize for battery life]		
April	320 [Accumulate, DO NOT Optimize for battery life]		
May	320 [Accumulate, DO NOT Optimize for battery life]		
June	320 [Accumulate, DO NOT Optimize for battery life]		
July	320 [Accumulate, DO NOT Optimize for battery life]		
August	320 [Accumulate, DO NOT Optimize for battery life]		
September	320 [Accumulate, DO NOT Optimize for battery life]		
October	320 [Accumulate, DO NOT Optimize for battery life]		
November	320 [Accumulate, DO NOT Optimize for battery life]		
December	320 [Accumulate, DO NOT Optimize for battery life]		
	Channel Settings		
Depth	Channel: 0; Range: -40m to 1000m; Resolution: 0.5m		
	0.0e0, 1.0, -194.0		
Correction factors	2.564e-6, 0.9038, 4.868		
	2.564e-6, 0.9038, 4.868 0.0e0, 1.0, 0.0		
Errors	2.564e-6, 0.9038, 4.868 0.0e0, 1.0, 0.0 None		
Errors Compensation factors	2.564e-6, 0.9038, 4.868 0.0e0, 1.0, 0.0 None -3.087e-9, 6.295e-6, -0.019, 25.37		
Errors Compensation factors Errors	2.564e-6, 0.9038, 4.868 0.0e0, 1.0, 0.0 None -3.087e-9, 6.295e-6, -0.019, 25.37 None		
Errors Compensation factors	2.564e-6, 0.9038, 4.868 0.0e0, 1.0, 0.0 None -3.087e-9, 6.295e-6, -0.019, 25.37 None Channel: 1; Range: -40C to 60C; Resolution: 0.05C		
Errors Compensation factors Errors	2.564e-6, 0.9038, 4.868 0.0e0, 1.0, 0.0 None -3.087e-9, 6.295e-6, -0.019, 25.37 None		
Errors Compensation factors Errors Temperature	2.564e-6, 0.9038, 4.868 0.0e0, 1.0, 0.0 None -3.087e-9, 6.295e-6, -0.019, 25.37 None Channel: 1; Range: -40C to 60C; Resolution: 0.05C 0.0e0, 1.0, 0.0		
Errors Compensation factors Errors Temperature Correction factors Errors	2.564e-6, 0.9038, 4.868 0.0e0, 1.0, 0.0 None -3.087e-9, 6.295e-6, -0.019, 25.37 None Channel: 1; Range: -40C to 60C; Resolution: 0.05C 0.0e0, 1.0, 0.0 0.0e0, 1.0, 0.0		
Errors Compensation factors Errors Temperature Correction factors	2.564e-6, 0.9038, 4.868 0.0e0, 1.0, 0.0 None -3.087e-9, 6.295e-6, -0.019, 25.37 None Channel: 1; Range: -40C to 60C; Resolution: 0.05C 0.0e0, 1.0, 0.0 0.0e0, 1.0, 0.0 0.0e0, 1.0, 0.0		
Errors Compensation factors Errors Temperature Correction factors Errors Light Level	2.564e-6, 0.9038, 4.868 0.0e0, 1.0, 0.0 None -3.087e-9, 6.295e-6, -0.019, 25.37 None Channel: 1; Range: -40C to 60C; Resolution: 0.05C 0.0e0, 1.0, 0.0 0.0e0, 1.0, 0.0 0.0e0, 1.0, 0.0 None Channel: 2; Range: 0 to 256; Resolution: 0.25 0.0e0, 1.0, 0.0		
Errors Compensation factors Errors Temperature Correction factors Errors	2.564e-6, 0.9038, 4.868 0.0e0, 1.0, 0.0 None -3.087e-9, 6.295e-6, -0.019, 25.37 None Channel: 1; Range: -40C to 60C; Resolution: 0.05C 0.0e0, 1.0, 0.0 0.0e0, 1.0, 0.0 0.0e0, 1.0, 0.0 None Channel: 2; Range: 0 to 256; Resolution: 0.25 0.0e0, 1.0, 0.0 0.0e0, 1.0, 0.0		
Errors Compensation factors Errors Temperature Correction factors Errors Light Level Correction factors	2.564e-6, 0.9038, 4.868 0.0e0, 1.0, 0.0 None -3.087e-9, 6.295e-6, -0.019, 25.37 None Channel: 1; Range: -40C to 60C; Resolution: 0.05C 0.0e0, 1.0, 0.0 0.0e0, 1.0, 0.0 0.0e0, 1.0, 0.0 None Channel: 2; Range: 0 to 256; Resolution: 0.25 0.0e0, 1.0, 0.0 0.0e0, 1.0, 0.0 0.0e0, 1.0, 0.0 0.0e0, 1.0, 0.0		
Errors Compensation factors Errors Temperature Correction factors Errors Light Level Correction factors Errors	2.564e-6, 0.9038, 4.868 0.0e0, 1.0, 0.0 None -3.087e-9, 6.295e-6, -0.019, 25.37 None Channel: 1; Range: -40C to 60C; Resolution: 0.05C 0.0e0, 1.0, 0.0 0.0e0, 1.0, 0.0 0.0e0, 1.0, 0.0 None Channel: 2; Range: 0 to 256; Resolution: 0.25 0.0e0, 1.0, 0.0 0.0e0, 1.0, 0.0 0.0e0, 1.0, 0.0 None		
Errors Compensation factors Errors Temperature Correction factors Errors Light Level Correction factors Errors Errors Compensation factors	2.564e-6, 0.9038, 4.868 0.0e0, 1.0, 0.0 None -3.087e-9, 6.295e-6, -0.019, 25.37 None Channel: 1; Range: -40C to 60C; Resolution: 0.05C 0.0e0, 1.0, 0.0 0.0e0, 1.0, 0.0 0.0e0, 1.0, 0.0 None Channel: 2; Range: 0 to 256; Resolution: 0.25 0.0e0, 1.0, 0.0 0.0e0, 1.0, 0.0 0.0e0, 1.0, 0.0 None None		
Errors Compensation factors Errors Temperature Correction factors Errors Light Level Correction factors Errors Errors Compensation factors Errors	2.564e-6, 0.9038, 4.868 0.0e0, 1.0, 0.0 None -3.087e-9, 6.295e-6, -0.019, 25.37 None Channel: 1; Range: -40C to 60C; Resolution: 0.05C 0.0e0, 1.0, 0.0 0.0e0, 1.0, 0.0 0.0e0, 1.0, 0.0 None Channel: 2; Range: 0 to 256; Resolution: 0.25 0.0e0, 1.0, 0.0 0.0e0, 1.0, 0.0 0.0e0, 1.0, 0.0 None None None		
Errors Compensation factors Errors Temperature Correction factors Errors Light Level Correction factors Errors Errors Compensation factors	2.564e-6, 0.9038, 4.868 0.0e0, 1.0, 0.0 None -3.087e-9, 6.295e-6, -0.019, 25.37 None Channel: 1; Range: -40C to 60C; Resolution: 0.05C 0.0e0, 1.0, 0.0 0.0e0, 1.0, 0.0 0.0e0, 1.0, 0.0 None Channel: 2; Range: 0 to 256; Resolution: 0.25 0.0e0, 1.0, 0.0 0.0e0, 1.0, 0.0 0.0e0, 1.0, 0.0 None 0.0e0, 0.0e0, 0.0, 0. None Channel: 6; Range: 0V to 5V; Resolution: 0.0049V		
Errors Compensation factors Errors Temperature Correction factors Errors Light Level Correction factors Errors Compensation factors Errors	2.564e-6, 0.9038, 4.868 0.0e0, 1.0, 0.0 None -3.087e-9, 6.295e-6, -0.019, 25.37 None Channel: 1; Range: -40C to 60C; Resolution: 0.05C 0.0e0, 1.0, 0.0 0.0e0, 1.0, 0.0 0.0e0, 1.0, 0.0 None Channel: 2; Range: 0 to 256; Resolution: 0.25 0.0e0, 1.0, 0.0 0.0e0, 1.0, 0.0 0.0e0, 1.0, 0.0 None None None		

	Errors	None
	Wet/Dry Sensor	Channel: 7; Range: 0 to 255; Resolution: 1
	Correction factors	0.0e0, 1.0, 0.0 0.0e0, 1.0, 0.0 0.0e0, 1.0, 0.0
	Errors	None
Deployment	memory area.	ionally be saved into the main archival feathers with black Tesa Tape
Immobilisation	-	2
Tag deployed on/at	05-11-29T03:00:00,	-66.669, 140.02
Tag retrieved on/at	-	
First transmission	05-11-23T04:30:00,	-66.662, 140.016
Last transmission	06-01-12T07:42:00,	-68.446, 156.874